



SQ20M0N0

COMBI OVEN 20 TRAYS - GN 1/1
MECHANICAL CONTROL
LINEAR SCALE



FUNCTIONAL CHARACTERISTICS

| | |
|------------------------------|------------------|
| Display | ANALOGIC |
| Supply | ELECTRIC |
| Timer | Linear |
| Number of motors | 4 |
| Motor speeds | 1 |
| Max cooking temperature (°C) | 260°C |
| Core probe | - |
| Cooking chamber material | AISI304 |
| Opening door | Right handle |
| Chimney | 50 mm open |
| Humidification | Direct injection |
| Air injection | - |
| Self-washing | - |

STANDARDS

| | |
|---------------|----|
| Certification | CE |
|---------------|----|

TRAYS

| | |
|---------------|------------------|
| Trays rack | Trolley PA 20/66 |
| Max tray load | 4 Kg |

DIMENSIONS

| | |
|-------------------------------------|--------------------|
| Oven size with handle WxDxH (mm) | 1051 X 1002 X 1900 |
| Oven size without handle WxDxH (mm) | 1051 X 938 X 1900 |
| Chamber size WxDxH (mm) | 700 X 481 X 1496 |
| Unit weight (Kg) | 250 |

PACKAGING

| | |
|---------------------------------|---------------------|
| Packaging | PALLET + CARTON BOX |
| Packaging size WxDxH (mm) | 1150 X 1100 X 2050 |
| Unit weight with packaging (Kg) | 273 |
| Crate packaging size (optional) | 1100 x 1150 x 2090 |
| Unit weight with crate (Kg) | 331 |



ELECTRICAL DATA

Heaters 6,75kW 50/60Hz
Single power supply

| | |
|--------------------------|--------------|
| Power | 28,1kW |
| Frequency | 50/60Hz |
| Power supply standard | 380-415V 3N~ |
| Amperage standard | 44,1A |
| Power cord req. standard | 5G10 |

Heaters 6,75kW 50/60Hz
Double power supply

| | |
|--------------------------|--------------------------|
| Power | 28,1kW |
| Frequency | 50/60Hz |
| Power supply optional | 380-415V 3N~/220-240V 3~ |
| Amperage optional | 44,1A / 72,03A |
| Power cord req. optional | 5G10/ 4G25 |

WATER CONNECTION REQUIREMENTS

| | |
|------------------------------------|---------------|
| Humidification Water Inlet | 3/4" GAS |
| Washing Water Inlet | - |
| Water drain | 2 x 30 mm |
| Max water hardness | 5°f |
| Water pressure requirement min-max | 150 - 200 kPa |

CONSUMPTION

| | |
|----------------------------|-------------------------|
| Humidification Water (L/h) | 15,7l/h max consumption |
| Rinse Water @2barG | - |
| Short Washing Water @2barG | - |
| Long Washing Water @2barG | - |
| Short Washing Detergent * | - |
| Long Washing Detergent * | - |

CONNECTIVITY

| | |
|-----------|---|
| USB | - |
| Bluetooth | - |
| Wi-Fi | - |
| Cloud | - |



ACCESSORIES

| | |
|----------------------------|----------------------|
| Self clean system kit | - |
| Oven stand | - |
| Hood (Air) | - |
| Hood (Water) | POSLMWF1 POSLMWF2 |
| Core Probe | - |
| Proofer | - |
| Stacking kit for 2 ovens | - |
| Smoker | SMK02 |
| Blast Chiller | - |
| Blast chiller stacking kit | - |
| Water softner cover | WS10 |
| Water softner 6800L | WS11 |
| Water softner 12000L | WS12 |
| Water pressure adapter | WPA |
| Water shower kit | S1 |
| Detergent 6KG | DT2 |
| Detergent 10KG | DT4 |

