



SQ05M0N0

COMBI OVEN 5 TRAYS - GN 1/1
MECHANICAL CONTROL
LINEAR SCALE



FUNCTIONAL CHARACTERISTICS

| | |
|------------------------------|------------------|
| Display | MECHANICAL |
| Supply | ELECTRIC |
| Timer | Linear |
| Number of motors | 2 |
| Motor speeds | 1 |
| Max cooking temperature (°C) | 260°C |
| Core probe | - |
| Cooking chamber material | AISI304 |
| Opening door | Right handle |
| Chimney | 50 mm open |
| Humidification | Direct injection |
| Air injection | - |
| Self-washing | - |

STANDARDS

| | |
|---------------|-------|
| Certification | CE-CB |
|---------------|-------|

TRAYS

| | |
|---------------|---|
| Trays rack | Wire GA 5/70 Sheet PA 5/85 (optional) Wire PA-BIV 5/80 (optional) |
| Max tray load | 4 kg |

DIMENSIONS

| | |
|-------------------------------------|-----------------|
| Oven size with handle WxDxH (mm) | 937 X 885 X 715 |
| Oven size without handle WxDxH (mm) | 937 X 821 X 715 |
| Chamber size WxDxH (mm) | 660 X 490 X 452 |
| Unit weight (Kg) | 86 |

PACKAGING

| | |
|---------------------------------|---------------------|
| Packaging | PALLET + CARTON BOX |
| Packaging size WxDxH (mm) | 1020 X 970 X 868 |
| Unit weight with packaging (Kg) | 102 |
| Crate packaging size (optional) | 1020 X 970 X 873 |



ELECTRICAL DATA

HEATERS 5kW 50/60Hz

| | |
|-----------------|--------------------------|
| Power | 10,5kW |
| Frequency | 50/60Hz |
| Power supply | 380-415V 3N~/220-240V 3~ |
| Amperage | 16,9A / 27,2A |
| Power cord req. | 5G4 / 4G4 |

HEATERS 6,5kW 50/60Hz

| | |
|-----------------|--------------------------|
| Power | 12,5kW |
| Frequency | 50/60Hz |
| Power supply | 380-415V 3N~/220-240V 3~ |
| Amperage | 19,7A / 32,03A |
| Power cord req. | 5G4 / 4G6 |

WATER CONNECTION REQUIREMENTS

| | |
|------------------------------------|-------------------|
| Humidification Water Inlet | 3/4" GAS |
| Washing Water Inlet | 8mm quick fitting |
| Water drain | 30 mm |
| Max water hardness | 5°f |
| Water pressure requirement min-max | 150-200 kPa |

CONSUMPTION

| | |
|----------------------------|------------------------|
| Humidification Water (L/h) | 7,8l/h max consumption |
| Rinse Water @2barG | - |
| Short Washing Water @2barG | - |
| Long Washing Water @2barG | - |
| Short Washing Detergent * | - |
| Long Washing Detergent * | - |

CONNECTIVITY

| | |
|-----------|---|
| USB | - |
| Bluetooth | - |
| Wi-Fi | - |
| Cloud | - |



ACCESSORIES

| | |
|----------------------------|--|
| Self clean system kit | - |
| Oven stand | TA9374H30X TA9374H40X - TA9374H40S TA9374H49X - TA9374H49S TA9374H70X - TA9374H70S TA9374H80X - TA9374H80S |
| Hood (Air) | POSQMAF1 POSQMAF2 |
| Hood (Water) | POSQMWF1 POSQMWF2 |
| Core Probe | - |
| Proofer | CA9308M0 CA9308MH CA9308DH CA9312M0 CA9312MH CA9312DH |
| Stacking kit for 2 ovens | SK42 |
| Smoker | SMK02 |
| Blast Chiller | KDA03 KDA05 |
| Blast chiller stacking kit | SK43 |
| Water softner cover | WS10 |
| Water softner 6800L | WS11 |
| Water softner 12000L | WS12 |
| Water pressure adapter | WPA |
| Water shower kit | S1 |
| Detergent 6KG | DT2 |
| Detergent 10KG | DT4 |

